



VACUUM TRUCK HOSE



WATER SUCTION HOSE

EPDM WATER SUCTION HOSE

Lightweight and flexible with abrasion resistant cover for agricultural chemicals and general industrial use. External helix provides for easy drag. Suitable for full vacuum.


Temperature Range
-40°C to +60°C (-40°F to +140°F)

Standard Lengths
100ft cut to multiples of 5ft at no charge



CHALLENGER CES

Lightweight and flexible hose with abrasion resistant cover for agricultural chemicals, general industrial use and oilfield service. Applications include liquid waste and septic handling. External helix provides low drag coefficient. Suitable for full vacuum.



Temperature Range
-40°C to +60°C (-40°F to +140°F)

Standard Lengths
1-1/2" to 6" - Max Length 100 ft. - Cut to 5 ft. multiples

PETROLEUM HOSE

POLAR MAXX - LOW TEMP TANK TRUCK HOSE

POLAR MAXX is an all purpose petroleum suction and discharge hose designed to remain flexible in low temperature conditions. The corrugated cover makes the hose very flexible and it is also suitable for full vacuum service.

Temperature Range
-50°C to +93°C (-58°F to +199°F)

Standard Lengths
100ft cut to multiples of 5ft



MATERIAL HANDLING HOSE

WEAR MAXX - HD INDUSTRIAL SUCTION HOSE

An extremely abrasion resistant hose designed for conveying wood, metal, rock, concrete, dust, etc. under vacuum. Corrugated for excellent flexibility.

Temperature Range
-40°C to +82°C (-40°F to +180°F)

Standard Lengths
6" & 8" - 100 ft.
10" - 40 ft.



WWW.CROSSCOUNTRYCANADA.CA
780-962-6559





SCORPION HOSE

SCORPION WATER HOSE

Scorpion Water is a premium hybrid garden hose with a polymer construction that allows this hose to remain flexible in cold temperatures. It is used as a hydraulic suction return line and is suitable for full vacuum service.



Temperature range
-40°C to 65°C (-40°F to 150°F)

Features

- 150 PSI
- Kink resistant when pressurized with water
- Crush proof heavy duty nickel brass fittings
- Lightweight & Durable
- Ideal for lawn & garden, landscapers and contractors.
- Abrasion Resistant
- Easy coiling after use

AIR HOSE

EXTRA PRESSURE MAXX HOSE

Extra Pressure MAXX is a robust heavy duty 400 PSI air/water hose for use in demanding environments such as mining, construction and industrial applications.

Temperature range
-30°C to +100°C (-22°F to +212°F)



Standard Lengths
50ft/ 100ft

CAM & GROOVE COUPLINGS

STAINLESS STEEL CAM & GROOVE COUPLINGS

Stainless steel cam type couplers are made of 316 Stainless Steel. Our most chemical and corrosion resistant cam type. Available in sizes from 1/2" to 6".



Specification

Body: 316 Stainless Steel
Arms: 304 Stainless Steel
Ring, Pin & Safety Pin: 202 Stainless Steel
Gasket: Black Nitrile

* Not for use with compressed air

FAT LIP LOCKING ARM CAMLOCKS



FAT LIP LOCKING ARM CAMLOCKS are designed for harsh fluid transfer applications. The locking arms reduce the risk of uncoupling during operation. The FAT LIP resists ovalizing during rough treatment.

High quality A356 aluminum with T6 heat treatment, make FAT LIP CAMS extremely durable. All cams are leak tested. MIL spec. MIL-A-A-59326. Available in sizes from 3" to 4".

Specification

Body: A356 Aluminum
Arms: Brass

* Not for use with compressed air